73 categories of Products...cutting edge HVAC solutions



(3.66 to 42.5 Tons)

JAUCIS ... cutting edge HVAC solution and the solution of the 0000


WCP Models Series

Sabro water-cooled self-contained air conditioners are single packaged air conditioners. These units are factory charged, properly tested and internally wired for rapid installation. The only work required at installation site is to mount the unit at place, connect the Duct--ing, electric supply, drain connection & cooling tower piping system.

These units are designed for installation inside building either in a plant room or directly inside the building either in a plant room or directly in conditioned space. The unit consists of compressor, condendser shell, evaporator coil, evaporator fan & motor and all other necessary electrical as well refrigeration controls which are equipped with accessories.

These units are designed to provide maximum efficiency at tropical conditions. If requird, the units can be provided with electric duct heater as an optional feature arrangements in supply ducting.

ON DEMAND, Larger Capacity Models are Available.











MODEL	COMP.	COMPRESSOR	AIR FLOW RATE	COOLING CAPACITY	
	HP	TYPE	CFM	BTU/HR	KCAL/HR
WCP 040-S	1x4.0	HermeticScroll	1200	44000	11095
WCP 050-S	1x5.0	HermeticScroll	1500	57000	14358
WCP 060-S	1x6.0	HermeticScroll	1800	63500	15995
WCP 080-S	1x8.0	HermeticScroll	2400	87500	22040
WCP 080-D	2x4.0	HermeticScroll	2300	88000	22166
WCP 100-D	2x5.0	HermeticScroll	3000	114000	28715
WCP 120-D	2x6.0	HermeticScroll	3600	127000	31990
WCP 160-S	1x16	HermeticScroll	4800	166500	41940
WCP 160-D	2x8.0	HermeticScroll	4900	170500	42947
WCP 200-D	2x10	HermeticScroll	6500	226000	56927
WCP 240-D	2x12	HermeticScroll	7500	259000	65239
WCP 320-D	2x16	HermeticScroll	9500	334000	84131
WCP 370-D	21+16	HermeticScroll	11000	385000	96977
WCP 420-D	2x21	HermeticScroll	12500	433000	109068
WCP 480-T	3x16	HermeticScroll	14500	498000	125441
WCP 500-D	2x25	HermeticScroll	15000	510000	128463

Capacities are based on, evaporator air in temp. at 80°F db(26.7°C), 67°F wb(19.5°C) & condenser water in temp 85°F db(29.4°C) Due to continuous improvement in our products, specs may change without notice.

honesty, integrity

good quality service

Longer product life

Sabro...
essential every day

www.sabrotechnology.com TEL: +92 51 4433006



