



Innovatively Creative ...
TRUST the AIRxperts

FCU Series

Fan Coil Units
with High EER

energy efficiency

Commercial & Industrial



55 Years of
SABRO

Cutting-edge HVAC Solutions
73 categories of HVAC Products




consistent performance





Cost effective

persistent optimization & performance verification



Aspire to inspire



Commercial Air Conditioning
proven, reliable control software



Available with Environmental Friendly Refrigerant + DC INVERTER



Innovatively Creative ...
TRUST the AIRxperts

FCU Series

Fan Coil Units with High EER

Commercial Type Air Conditioners

FCU Series

Fan Coil Units

Sabro made fan coil units provide cooling/heating air for all commercial/industrial air-conditioning applications. Sabro FCU Series models are suitable to maintain stable cooling. These units are design to provide maximum cooling/heating efficiency at tropical conditions.

Fan coil are used for installation in any commercial building, industrial application, hotel, motel, office, hospital and restaurant as well for large residences to provide required temperature and air flow for each individual room.

Fan-coil units provide heating, cooling, or both to individual spaces. They may be mounted in free standing cabinets, walls, in ceiling plenums, or in other locations. Fan-coil units usually discharge air directly from their enclosures, although some may be installed with short ducts. It ranges from capacities i.e. 300CFM to 2000CFM. These units are available in multiple categories. These units are constructed rugged and strong, yet are light and compact for installation on ceiling or on floor. It is desirable to operate on a centralized production of chilled water. The units are connected with chiller and hot water generator combined with each air conditioned space (air or water regulation of each fan coil unit).

These units provide advantage of setting different temperatures for each room. It also results in energy saving by switching off the units of an empty room.

MODEL	AIR FLOW RATE	WATER FLOW GPM	CAPACITY COOLING BTU/HR (KCAL/HR)
FCU 300	300	1.8	9000 (2270)
FCU 400	400	2.4	12000 (3026)
FCU 600	600	3.6	18000 (4539)
FCU 800	800	4.8	24000 (6052)
FCU 1000	1000	6.0	30000 (7565)
FCU 1200	1200	7.2	36000 (9078)
FCU 1600	1600	9.6	48000 (12104)
FCU 2000	2000	12.0	60000 (15130)

ON DEMAND - Higher Capacities Models Are Available.

honesty, integrity

Sabro... good quality service longer product life
essential every day

Made In
PAKISTAN
Since 1969

www.sabrotechnology.com
Phone: +92 51 4433006

